PRODUCT INFORMATION

REGUPOL terrace solid

Application

Protective layers for use underneath mounting systems for terraces, balconies and loggias

Product

Name of Product	**REGUPOL terrace solid**
Colour	multicolored
Material	elastic premanufactured mat made from butyl-rubber, bound with polyurethane
Thickness	6 mm (larger material thicknesses possible on request)

Technical Data

Specific Weight	1062 kg/m³	
Weight per m²	6.37 kg	
Tensile Strength	≥ 0.60 N/mm²	following DIN EN ISO 1798
Elongation at Break	≥ 60 %	following DIN EN ISO 1798
Temperature Resistance	- 40° C up to 115° C	
Fire Resistance	Class E	DIN EN 13501-1
Certification		

Notice: The above-mentioned test data are based on periodical laboratory testing of test specimen taken from the actual manufacturing process and show the average values measured. The publishing of these technical data does not relieve the user of the necessity to test the relevant product for physical fitness based on a specific application. As the final use and application of our products are out of our control, this is the sole responsibility of the buyer / end user. All our products do carry a warranty against manufacturer's defects according to our standard terms and conditions of sale. Due to deviations in raw materials, external influences like temperature and humidity variations, and the fact that this data relates to a resilient material the above-mentioned values are subject to vary up to +/- 25%.